

L-SP3 Security Pedestal



BREAKTHROUGH PERFORMANCE

Based on the industry leading TAGSYS Medio L400 electronics, the L-SP3 security pedestal uses advances in Digital Signal Processing (DSP) and RF Front End technology to achieve breakthrough performance in read range and read speed with industry leading signal to noise ratio.

LSP3 is compatible with TAGSYS' Visual Count software enabling statistics and reports on patron traffic in and out the library.

TWO VERSIONS FOR A MULTITUDE OF ENVIRONMENTS

Available in two standard versions, the L-SP3 platform provides customers the flexibility to match performance and aesthetic requirements based on the application:

- L-SP3 - Based on the industry proven L-SP2 look and feel, this version is the solution for customers looking for a high performance, cost effective RFID security system.
- L-SP3 Clear - Designed for environments where aesthetics are a key factor, the clear L-SP3 version couples a sleek profile and high quality acrylic panel with high performance electronics to achieve a best in breed RFID security system.

TAGSYS provides complete, reliable, high performance RFID infrastructure systems for item-level tracking in a variety of industries.

Our unique RFID expertise, combined with a true understanding of RFID business processes, make us the ideal RFID partner to ease and ensure the success of your project.

More information on TAGSYS can be found at: www.tagsysrfid.com



L-SP3 Clear



L-SP3

TAGSYS USA
1006 W. 9th Avenue
Suite 30
King of Prussia, PA 19406
USA
Phone: (+1) 267 882 4800

TAGSYS France
785 Voie Antiope - Athélia III
13600 La Ciotat
France
Phone: (+33) 4 42 18 89 00

TAGSYS Asia
Unit A, 11/F, On Hing Building
1 On Hing Terrace
Central Hong Kong
Phone: (+852) 2526 8303

www.tagsysrfid.com

Copyrights © TAGSYS 2011
This document and the information
it contains are the exclusive property
of TAGSYS. All Rights Reserved. Any
unauthorized
reproduction is strictly prohibited.

T-M-LSP3-Datasheet-6dec2011

PRODUCT SPECIFICATIONS

ELECTRICAL

CHIP COMPATIBILITY:

TAGSYS C370 (NXP SLI), C370-L (NXP SLI-L), Tag-it™HFI (Texas Instruments),
ISO 15693 supporting AFI and read multiple bloc command

SECURITY MODES:

EAS and AFI

COMMUNICATION INTERFACE:

Ethernet

POWER SUPPLY:

85 to 265 VAC/ 50-60 Hz

ALARMS :

Lights and Buzzer

PEOPLE COUNTER:

Integrated bi-directional (counts in and out traffic)
Optional: TAGSYS' Visual Count software suite.

L-SP3 MECHANICAL

COMPONENTS:

One pedestal including the integrated antenna and the electronics unit (controller)

DIMENSIONS:

1782 x 556 x 45 mm (70.2 x 21.9 x 1.8 inches)

Base Plate: 620 x 80 mm (24.4 x 3.1 inches)

MATERIALS:

High Quality Plastic UL 94 HB

PANEL COLOR:

Two-tone Gray

L-SP3 CLEAR MECHANICAL

COMPONENTS:

One pedestal including the integrated antenna and the electronics unit (controller)

DIMENSIONS:

1846 x 546 x 45 mm (72.6 x 21.5 x 1.8 inches)

Base Plate: 620 x 80 mm (24.4 x 3.1 inches)

MATERIALS:

High Quality Acrylic UL 94 HB

CERTIFICATIONS

ETSI EN 300 330 (EM Emission)
ETSI EN 301 489 (EM Immunity)
ETSI EN 50364 (Human Exposure)
EN 60950 (Electrical Safety)
FCC ID pending
IC (Industry Canada) pending
UL, c-UL & CB pending
C-Tick pending